



BiPAC 8207AZ 5G

5G NR Embedded V/ADSL2+ AX1500 VPN Firewall Router

The BiPAC 8207AZ 5G, triple-WAN, EWAN, 5G NR(sub-6GHz) and VDSL&ADSL2+ firewall router integrates the 802.11ax (5GHz) + 802.11n (2.4GHz) Wireless Access Point and Giga switch. BiPAC 8207AZ 5G embedded with 5G NR module backward compatibility with 4G LTE, also provides Gigabit Ethernet WAN interfaces, with an integrated 802.11n/ax dual-band wireless access point and 4-port Gigabit Ethernet LAN (3 ports Gigabit switch ports and extra one Giga Ethernet port can be as LAN or EWAN port), enables high-speed and secured Internet connectivity for home, SOHO, and enterprise users.

5G NR Mobility

With the newest 5G NR network connectivity, users can enjoy an unprecedented Internet accessing experience.

Smooth, Responsive Net Connection

Quality of Service (QoS) gives user full control over outgoing data traffic. Priority can be assigned by the router to ensure that important transmissions like gaming packets, calls or IPTV/streaming content passes through the router at lightning speed, even when there is heavy Internet traffic. The speed of different types of outgoing data passing through the router is also controlled to ensure that users do not saturate bandwidth with their browsing activities.

Maximum Performance Dual-band Wireless Router

Featured with simultaneous dual-band technology, the BiPAC 8207AZ 5G can run both 2.4GHz and 5GHz frequency bands at the same time, offering ultra-fast wireless speeds of up to 1200Mbps (5GHz) and 300Mbps (2.4GHz), and SSIDs on both bands. The BiPAC 8207AZ 5G, by adopting this state-of-the-art technology, allows for multiple-demand applications, such as streaming HD videos and multiplayer gaming simultaneously. The Wireless Protected Access (WPA-PSK/WPA2-PSK) and Wireless Encryption Protocol (WEP) features enhance the level of transmission security and access control over wireless LAN. The router also supports the Wi-Fi Protected Setup (WPS) standard, allowing users to establish a secure wireless network by simply pushing a button.

Experience Gigabit

The BiPAC 8207AZ 5G has 3 ports Gigabit switch ports and extra one Giga Ethernet port can be as LAN or EWAN port. This EWAN offers another broadband connectivity option for connecting to a cable, DSL, fiber modem.

Secure VPN Connections

The BiPAC 8207AZ 5G supports embedded IPSec VPN (Virtual Private Network) protocols, allowing users to establish encrypted private connections over the Internet. You can access your corporate Intranet and transmit sensitive data between branch offices and remote sites anytime; even when you are out of office, thus enhancing productivity.

- ✓ Compliant with VDSL2/ADSL2+ standards
- ✓ Triple-WAN ports for 5G NR, VDSL2/ADSL2+, Gigabit Ethernet WAN (EWAN) for broadband connectivity
- ✓ Load balance among multiple WAN interfaces
- ✓ Embedded 5G NR(sub-6GHz) and SIM slot
- ✓ Simultaneous dual-band Wireless 1200Mbps (5GHz) and 300Mbps (2.4GHz)
- ✓ Gigabit EWAN and LAN ports
- ✓ IPv6 ready (IPv4/IPv6 dual stacks)
- ✓ Fibre (FTTC/FTTP/FTTH) ready with high WAN throughput via EWAN port
- ✓ NBN (National Broadband Network) ready*1
- ✓ USB port for storage.
- ✓ QoS for traffic prioritization and bandwidth management
- ✓ Secure VPN with powerful DES/3DES/AES
- ✓ Compliant with IEEE 802.11a/b/g/n and 802.11ac/ax standards
- ✓ Supports MU-MIMO and mesh
- ✓ WPS (Wi-Fi Protected Setup) for easy setup
- ✓ Wireless security with WPA-PSK/WPA2-PSK
- ✓ Multiple wireless SSIDs with wireless guest access and client isolation
- ✓ Supports Bridge Grouping
- ✓ SOHO firewall security
- ✓ Auto failover and failback
- ✓ Supports IPTV application*2
- ✓ Ideal for home, SOHO, retail stores

Features & Specifications

VDSL2/ADSL2+ Compliance

- Compliant with xDSL standard
 - ITU-T G.993.2 (VDSL2)
 - ITU-T G.998.4 (G.inp)
 - ITU-T G.993.5 (G.vector)
 - ITU-T G.992.3 (G.dmt.bis) Annex A, B, I, J, L and M.
 - ITU-T G.992.5 (G.dmt.bis plus)
 - Full-rate ANSI T1.413 Issue 2
 - ITU-T G.992.1 (G.dmt) Annex A, B
 - ITU-T G.992.2 (G.lite) Annex A, B
- Supports VDSL2 band plan: 997 and 998
- ADSL2/2+ fallback modes
- Supports VDSL2 profiles: 8a, 8b, 8c, 8d, 12a, 12b, 17a, 30a and 35b.
- Supports ATM and PTM modes
- Supports Dying Gasp

Supported Frequency Bands^{*3}

- Embedded 5G NR sub-6GHz
 - Frequency bands and data rate depend on equipped 5G NR(sub-6GHz) module
 - Support both 5G NSA and SA modes.
 - 5G NR SA:
 - n1/n2/n3/n5/n7/n8/n12/n13/n14/n18/n20/n25/n26/n28/n29/n30/n38/n40/n41/n48/n66/n70/n71/n75/n76/n77/n78/n79
 - 5G NR NSA:
 - n1/n2/n3/n5/n7/n8/n12/n13/n14/n18/n20/n25/n26/n28/n29/n30/n38/n40/n41/n48/n66/n70/n71/n75/n76/n77/n78/n79
- 4G LTE:
 - FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B18/B19/B20/B25/B26/B28/B29/B30/B32/B66/B71
 - TDD: B34/B38/B39/B40/B41/B42/B43/B46(LAA)/B48

Network Protocols and Features

- IPv4 or IPv4/IPv6 dual stack
- NAT, static (v4/v6) routing and RIP-1/2
- IPv6 stateless/stateful address auto-configuration
- IPv6 router advertisement
- IPv6 over PPP
- DHCPv6
- IP tunnel IPv6 in IPv4 (6RD)
- IP tunnel IPv4 in IPv6 (DS-Lite)
- Universal Plug and Play (UPnP) compliant
- Dynamic Domain Name System (DDNS)
- Virtual server and DMZ
- SNTP, DNS relay, IGMP proxy and IGMP snooping for video service
- MLD proxy and MLD snooping for video service
- Management based on IP protocol, port number and address
- Supports Bridge Grouping

Firewall

- Built-in NAT firewall
- Prevents DoS attacks including Land Attack, Ping of Death, etc

Virtual Private Network (VPN)

- IPSec VPN tunnels
- IKE key management
- DES, 3DES and AES encryption for IPSec
- IPSec pass-through
- GRE (Generic Routing Encapsulation) tunnel
- Supports L2TP, PPTP, and L2TP over IPsec.
- Supports OpenVPN.

Quality of Service Control

- Supports the DiffServ approach
- Traffic prioritization and bandwidth management based on IP protocol, port number and address

ATM and PPP Protocols

- Compliant with xDSL standard
- ATM Adaptation Layer Type 5 (AAL5)
- Multiple protocol over AAL5 (RFC 2684, formerly RFC 1483)
- Bridged or routed Ethernet encapsulation
- VC-based and LLC-based multiplexing
- PPP over Ethernet (PPPoE)
- PPP over ATM (RFC 2364)
- Classical IP over ATM (RFC 1577)
- MAC encapsulated routing (RFC 1483 MER)
- OAM F4/F5

IPTV Applications^{*2}

- IGMP snooping and IGMP proxy
- MLD snooping and MLD proxy
- Bridge Grouping
- Supports VLAN MUX
- Quality of Service (QoS)

Wireless LAN

- Compliant with IEEE 802.11a/b/g/n/ac/ax standards
- 2.4 GHz and 5 GHz frequency range
- Up to 1500Mbps wireless operation rate
- WPS (Wi-Fi Protected Setup) for easy setup
- Supports WPS
- 64/128 bits WEP supported for encryption
- Wireless security with WPA-PSK/WPA2-PSK
- Multiple wireless SSIDs with wireless guest access and client isolation

USB Application Server

- Storage/NAS: FTP server, Samba server (V1 & V2)

Management

- Web-based GUI for remote and local management (IPv4/IPv6)
- Firmware upgrade and configuration data upload and download via web-based GUI
- Embedded Telnet server for remote and local management
- Supports SNMP
- Supports DHCP server/client/relay
- TR-069^{*4} supports remote management
- Load balance
- Auto failover and failback

Hardware Specifications

Physical Interface

- WLAN: 2 external antennas
- 5G NR(FR1): 4 external antennas
- DSL port
- USB 2.0 port
- Ethernet: 3-port 10/100/1000M auto-crossover (MDI/MDI-X) switch
 - Extra one Giga Ethernet ports can be configured as a LAN or EWAN interface for broadband connectivity
- SIM slot
- Factory default reset button
- WPS push button
- Power jack
- Power switch

Physical Specifications

- Dimensions: 9.04" x 6.10" x 1.69"
(229.5 mm x 155 mm x 43 mm)

Power Requirements

- Input: 15V DC, 2A

Operating Environment

- Operating temperature: 0°C ~ 40°C
- Storage temperature: -20°C ~ 70°C
- Humidity: 20% ~ 95% non-condensing

*Notes:

- This is only applicable for Australia and New Zealand.
- Only upon request for Telco / ISP tender projects.
- The 5G NR is dependent on your local service provider.
- On request for Telco / ISP projects
- Specifications in this datasheet are subject to change without prior notice